



TECHNICAL PARAMETERS

ITEM		UNIT	CDM6376
Basic	Operating weight	kg	39300
	Boom length	mm	6500
	Arm length	mm	2800
	Standard bucket	m ³	1.9m ³ (rock)
	Max.Travel speed	km/h	3.5-5.5
	Max.Swing speed	rpm	8.8
	Grade ability	°	35(70%)
	Ground pressure	kPa	68.8
	Max.Traction force	kN	334
Engine	Engine model	—	GH-6HK1
	Rated power	kW/rpm	212/2000
	Max.Torque	Nm/rpm	1080/1500
	Displacement	L	7.79
	Fuel tank	L	600
Hydraulic	Max.Flow(Main pump)	L/min	324×2
	Working pressure	MPa	34.3
	Max.Pilot pressure	MPa	3.9
	Max.Arm digging force	kN	210
	Max.Bucket digging force	kN	235
Hrdraulic oil tank	L	300	
Chassis	Track width	mm	600
	Track shoes number	—	49×2
	Carrier rollers number	—	2×2
	Track rollers number	—	9×2
Electric	System voltage	V	24
	Battery capacity	V/Ah	24/165×2

PRODUCT FEATURES

Isuzu Turbocharged Engine, Large Displacement, Strong Power
Optimized Cooling System to Reduce Power Loss and Noise
Advanced Hydraulic Control System
Combined C type closed frame improves rigidity and strength of rotary platform.
Comfortable ROPS Cabin with 2.7m ³ Operational Space
No Frame Cab Glasses to Enlarge Operation Field of View
Rock Track Shoes, Chassis Reinforcement, More reliable and Wear-resistant
Heavy-duty Working Device with High Strength Low Alloyed Steels

OPTIONAL

Breaking hammer & pipeline
Work warning light
Walking alarm
Top protecting net
Front protecting net
700mm triple grouser shoes
800mm triple grouser shoes

The following blank can be used for notes or comments.

**For more information on Lonking products,
Please contact our local agent:**

LONGKING 龙工



CDM6376 HYDRAULIC EXCAVATOR

Efficiency Rules the Future



LONGKING (FU JIAN) INTERNATIONAL TRADE CO., LTD.
LONGKING HOLDINGS LIMITED

OPERATING WEIGHT:	39300kg
ENGINE POWER:	212kW
BUCKET CAPACITY:	1.9m ³
TRAVEL SPEED:	3.5/5.5km/h